

MAY 22 2006

Appln. No. 10/611,742

Attorney Docket No. 10541-1797

## I. Amendments to the Claims

## 1. (Cancelled)

2. (Previously Presented) A system adapted to eliminate undesired sounds during turn on of a FM modulator, the FM modulator having a RF output signal in communication with a radio receiver, a VCO modulation input, and a composite output signal, the system comprising:

a RF attenuator circuit in communication with the RF output signal of the FM modulator and adapted to initially reduce the RF output signal;

a RF ramp up circuit in communication with the RF attenuator circuit and adapted to deactivate the RF attenuator circuit;

a delay switch circuit in communication with the RF ramp up circuit and adapted to delay activation of the RF ramp up circuit; and

an audio ramp up circuit in communication with the RF ramp-up circuit and the composite output signal of the FM modulator, the audio ramp up circuit increasing the composite output signal.

3. (Original) The system according to Claim 2, the audio ramp up circuit including a resistor, a capacitor, and a transistor.

4. (Previously Presented) A system adapted to eliminate undesired sounds during turn on of a FM modulator, the FM modulator having a RF output signal in communication with a radio receiver, a VCO modulation input, and a composite output signal, the system comprising:

a RF attenuator circuit in communication with the RF output signal of the FM modulator and adapted to initially reduce the RF output signal;

a RF ramp up circuit in communication with the RF attenuator circuit and adapted to deactivate the RF attenuator circuit; and

a delay switch circuit in communication with the RF ramp up circuit and adapted to delay activation of the RF ramp up circuit; and



BRINKS HOFER GILSON & LIONE  
PO Box 10385  
Chicago, IL 60610

Appln. No. 10/611,742

Attorney Docket No. 10541-1797

wherein a first side of the resistor is in communication with the delay switch circuit, a second side of the resistor is in communication with the capacitor and the transistor, the capacitor being connected between the resistor and an electrical ground.

5. (Original) The system according to Claim 4, the transistor of the audio ramp up circuit including a gate, a source, and a drain, wherein the gate is in communication with the resistor and the capacitor, the source is in connection with the composite output signal of the FM modulator, and the drain is in connection with the VCO modulation input.

6. (Cancelled)

7. (Previously Presented) The system according to Claim 8, wherein the transistor is a PNP transistor.

8. (Previously Presented) A system adapted to eliminate undesired sounds during turn on of a FM modulator, the FM modulator having a RF output signal in communication with a radio receiver, a VCO modulation input, and a composite output signal, the system comprising:

a RF attenuator circuit in communication with the RF output signal of the FM modulator and adapted to initially reduce the RF output signal;

a RF ramp up circuit in communication with the RF attenuator circuit and adapted to deactivate the RF attenuator circuit; and

a delay switch circuit in communication with the RF ramp up circuit and adapted to delay activation of the RF ramp up circuit, the RF attenuator circuit including a transistor, the transistor having a base, a collector, and an emitter; and



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appl. No. 10/611,742

Attorney Docket No. 10541-1797

wherein the emitter is connected to a power source, the base is in communication with the RF ramp up circuit, and a collector is in communication with the RF signal of the FM modulator.

9. (Cancelled)

10. (Previously Presented) A system adapted to eliminate undesired sounds during turn on of a FM modulator, the FM modulator having a RF output signal in communication with a radio receiver, a VCO modulation input, and a composite output signal, the system comprising:

a RF attenuator circuit in communication with the RF output signal of the FM modulator and adapted to initially reduce the RF output signal;

a RF ramp up circuit in communication with the RF attenuator circuit and adapted to deactivate the RF attenuator circuit, the RF ramp up circuit including a capacitor and a first resistor;

a delay switch circuit in communication with the RF ramp up circuit and adapted to delay activation of the RF ramp up circuit; and

wherein a first side of the capacitor is in communication with an electrical ground and a second side of the capacitor is in communication with the first resistor and the delay switch circuit, the first resistor being connected between a voltage source and the RF attenuator circuit.

11. (Previously Presented) The system according to Claim 2, the time delay switch circuit including a first and second transistor, a resistor, and a capacitor.

12. (Original) The system according to Claim 11, wherein the second transistor is a NPN transistor.



BRINKS HOFER GILSON & LYONE  
PO Box 10395  
Chicago, IL 60610

Appln. No. 10/611,742

Attorney Docket No. 10541-1797

13. (Original) The system according to Claim 11, the NPN transistor having a base in communication with the second transistor, an emitter in communication with an electrical ground, and a collector in communication with the RF ramp-up circuit.

14. (Original) The system according to Claim 11, wherein the second transistor is a field effect transistor, the gate of the field effect transistor being in communication with the resistor and the capacitor, the source of the field effect transistor being in communication with an electrical ground, and the drain of the field effect transistor being in communication with the first transistor.

15. (Original) The system according to Claim 8, further comprising an audio ramp up circuit in communication with the delay switch circuit and the composite output of the FM modulator.

16. (Original) The system according to Claim 15, the audio ramp up circuit including a resistor, a capacitor, and a second transistor.

17. (Original) The system according to Claim 16, wherein a first side of the resistor is in communication with the delay switch circuit, a second side of the resistor is in communication with the capacitor and the second transistor, the capacitor being connected between the resistor and an electrical ground.

18. (Original) The system according to Claim 17, the second transistor of the audio ramp up circuit including a gate, a source, and a drain, wherein the gate is in communication with the resistor and the capacitor, the source is in connection with the composite output signal of the FM modulator, and the drain is in connection with the VCO modulation input of the FM modulator.



BRINKS HOFER GILSON & LIONE  
PO Box 10395  
Chicago, IL 60610

Appln. No. 10/611,742

Attorney Docket No. 10541-1797

19. (Original) The system according to Claim 8, the RF ramp up circuit including a capacitor and a first resistor.

20. (Original) The system according to Claim 19, wherein a first side of the capacitor is in communication with an electrical ground and a second side of the capacitor is in communication with the first resistor and the delay switch circuit, the first resistor being connected between a voltage source and the RF attenuator circuit.

21. (Original) The system according to Claim 20, the RF ramp-up circuit including a second resistor, the second resistor being connected between the RF attenuator and the delay switch circuit.

22. (Previously Presented) The system according to Claim 8, the time delay switch circuit including a second and third transistor, a resistor, and a capacitor.

23. (Original) The system according to Claim 22, wherein the second transistor is a NPN transistor, the NPN transistor having a base in communication with the third transistor, a emitter in communication with an electrical ground, and a collector in communication with the RF ramp-up circuit.

24. (Original) The system according to Claim 22, wherein the third transistor is a field effect transistor, the gate of the field effect transistor being in communication with the resistor and the capacitor, the source of the field effect transistor being in communication with an electrical ground, and the drain of the field effect transistor being in communication with the second transistor.

25-32 (Cancelled).



BRINKS HOFER GILSON & LIONE  
PO Box 10385  
Chicago, IL 60610